




B04843



Quote:

A: 76 I: 54
B: 154 L: 118
C: 74,5
D: 22
E: 138
F: 112
G: 72
H: 114



IP56 03 VM Watertight wall junction box with GRAY metal screws

Technical properties

Materials

| | |
|-----------|---------------|
| RAL color | Gray RAL 7035 |
| Material | ABS |

Dimensions

| | |
|--------|--------|
| Depth | 70 mm |
| Length | 150 mm |
| Length | 110 mm |

Installation, assembly

| | |
|-----------------|-------------------------|
| Mounting method | wall / ceiling mounting |
|-----------------|-------------------------|

Accessories included

| | |
|------|-------|
| With | Other |
|------|-------|

Equipment

| | |
|-------------|-------|
| Cable entry | Other |
|-------------|-------|

Standards, Approvals

| | |
|-------------------------|-------------------------|
| Reference standards | EN 60670-22 |
| European RoHs directive | voluntary compatibility |

Safety

| | | |
|---|-------------------------------------|------|
| Degree of protection of the casing | Degree | IP56 |
| of resistance to incandescent wire Halogen-free | according to EN 60695-2-11: 650 ° C | Yes |
| Impact resistance | | IK07 |
| Resistant to ultraviolet. Fire resistance | | Yes |
| | | - |

Conditions of use

| | |
|-----------------------|-----------------|
| Operating temperature | - 25 ... 60 ° C |
|-----------------------|-----------------|

Form

| | |
|------|-------------|
| Form | Rectangular |
|------|-------------|