
Product sheets B04849

:hager (B) восснютти



B04849



RAL color	Gray RAL 7035
Material	ABS
Dimensions	
Depth	160 mm
Length	240 mm
Length	190 mm
Installation, assembly	
Mounting method	wall / ceiling mounting
Accessories included	
With	Othe
Equipment	
Cable entry	Othe
Standards, Approvals	
Reference standards	
	EN 60670-22
European RoHs directive	
European RoHs directive Safety	voluntary compatibility
European RoHs directive Safety Degree of protection of the casing Degree	voluntary compatibility IP56
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen-	voluntary compatibility IP56 according to EN 60695-2-11: 650 ° C
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen- free	voluntary compatibility IP56 according to EN 60695-2-11: 650 ° C Yes
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen- free Impact resistance	voluntary compatibility IP56 according to EN 60695-2-11: 650 ° 0 Yes IK08
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen- free Impact resistance Ultraviolet resistant Fire	voluntary compatibility IP56 according to EN 60695-2-11: 650 ° C Yes IK08
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen- free Impact resistance Ultraviolet resistant Fire resistance	voluntary compatibility IP56 according to EN 60695-2-11: 650 ° 0 Yes IK08
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen- free Impact resistance	voluntary compatibility IP56 according to EN 60695-2-11: 650 ° C Yes IK08 Yes
European RoHs directive Safety Degree of protection of the casing Degree of resistance to incandescent wire Halogen- free Impact resistance Ultraviolet resistant Fire resistance Conditions of use	EN 60670-22 voluntary compatibility IP56 according to EN 60695-2-11: 650 ° C Yes IK08 Yes - 25 60 ° C

IP56 05 CA VM Junction box with high cover metal screws GRAY

Technical properties