



Main

| | |
|---------------------------|--|
| Range | ClimaSys |
| Product name | ClimaSys CV |
| Product or component type | Fan |
| Type of filter | Standard |
| Flow rate | Free flow rate with standard filter: 58 m ³ /h at 50 Hz |
| [Us] rated supply voltage | 10...27.6 V |
| Input voltage | 24 V DC 50/60 Hz |

Complementary

| | |
|---------------------------------------|---|
| Absorbed power | 3.6 W 50 Hz |
| [In] rated current | 0.18 A 50 Hz |
| Noise level < at | 40...41 dB |
| Bearing type | Ball |
| Height | 137 mm external: |
| Width | 117 mm external: |
| Depth | 49 mm external: |
| Cut-out dimensions | 92 x 92 mm |
| Net weight | 0.23 kg |
| Material | Outlet grille: injected thermoplastic (ASA PC) |
| Colour | Outlet grille: grey (RAL 7035) |
| Ambient air temperature for operation | -10...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Maximum pressure | 29 Pa flow rate 0 m ³ /h |
| Connections - terminals | Cable |
| IP degree of protection | IP54 |
| Device composition | 1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template |
| Condition of use | Flow rates depends on the work point, see ProClima software Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

Warranty

18 months
