

ENSTO

Additional pole

KS1.16

Code	KS1.16
GTIN	6418677171253
Name	Additional pole Ensto Compact 16 A, for panel or DIN-rail mounted switch
Description	Accessory for Ensto Compact switches
Vendor	Ensto Building Systems Finland Oy



Technical specification

Certificates

Standards: EN 60947-3

Dimensions

Size:	18 x 56 x 75
Length:	72 mm
Volume :	7.56 cm ³
Conductor cross-section:	Cu 1.5-16
Width:	13 mm
Height:	56 mm
Net Weight:	0.046 kg

Electrical values

Breaking capacity 415 V, AC 23 A:	128 A
Making capacity 415 V, AC 23 A:	160 A
Rated insulation voltage:	800 V
Rated operational current:	AC 22 A: 415V / 16A, 500V / 16A, 690V / 16A, AC 23 A: 415V / 16A, 500V / 16A, 690V / 16A

Mechanical

Tightening torque:	2 Nm
--------------------	------

Short-circuit characteristics

Max. cut-off current:	6 kA
Max. fuse:	16 A
Max. Joule integral:	6.8 kA ² s

Rated conditional short-circuit current: 50 kA
Rated short time withstand current: 1260 A (1 s)

Others

ETIM Class: EC002498

ETIM Technical specification

etim

Type of accessory: 4th pole pole

Packaging

Pallet package

Unit: pcs
Package size: 5250
Depth: 1200 mm
Width: 800 mm
Height: 1032 mm

Default package

Unit: pcs
Package size: 50
Depth: 218 mm
Width: 218 mm
Height: 126 mm
Weight: 2.622 kg
Volume: 5.988024 l