

ENSTO

Additional pole

KS1.25

| | |
|-------------|---|
| Code | KS1.25 |
| GTIN | 6418677170065 |
| Name | Additional pole Ensto Compact 25 A, for panel or DIN-rail mounted switch |
| Description | Accessory for Ensto Compact switches |
| Vendor | Ensto Building Systems Finland Oy |



Technical specification

Certificates

Standards: EN 60947-3

Dimensions

| | |
|--------------------------|----------------------|
| Size: | 18 x 56 x 75 |
| Length: | 72 mm |
| Volume : | 7.56 cm ³ |
| Conductor cross-section: | Cu 1.5-16 |
| Width: | 13 mm |
| Height: | 56 mm |
| Net Weight: | 0.046 kg |

Electrical values

| | |
|-----------------------------------|---|
| Breaking capacity 415 V, AC 23 A: | 200 A |
| Making capacity 415 V, AC 23 A: | 250 A |
| Rated insulation voltage: | 800 V |
| Rated operational current: | AC 22 A: 415V / 25A, 500V / 25A, 690V / 25A, AC 23 A: 415V / 25A, 500V / 25A, 690V / 25A |

Mechanical

Tightening torque: 2 Nm

Short-circuit characteristics

| | |
|-----------------------|-----------------------|
| Max. cut-off current: | 6 kA |
| Max. fuse: | 25 A |
| Max. Joule integral: | 6.8 kA ² s |

Rated conditional short-circuit current: 50 kA
Rated short time withstand current: 1260 A (1 s)

Others

ETIM Class: EC002498

ETIM Technical specification

etim

Type of accessory: 4th pole pole

Packaging

Pallet package

Unit: pcs
Package size: 5250
Depth: 1200 mm
Width: 800 mm
Height: 1032 mm

Default package

Unit: pcs
Package size: 50
Depth: 218 mm
Width: 218 mm
Height: 126 mm
Weight: 2.622 kg
Volume: 5.988024 l