

Product datasheet

Specifications



Spacial S3DEX (ATEX certified) H600xW600xD250 .IP66 IK10 RAL7035.

Local distributor code: 392867676 NSYS3DEX6625

EAN Code : 3606480158612

Main

Range	Spacial
Product name	Spacial S3DEX
Application	ATEX certified application
Category	Compact enclosure
Enclosure nominal height	600 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	250 mm
Door type	Plain
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting
Product destination	For potentially explosive atmosphere
Device composition	1 door 1 lock body with clamped blind nut

Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Steel
Surface finish	Epoxy-polyester powder
Colour	Grey (RAL 7035)
Standards	EN 60079-0:2012 EN 60079-7:2007 EN 60079-31:2009
Marking	II 2 GD Ex e IIC Gb Ex tb IIIC Db according to the ATEX directive 94/9/EC
Net weight	15.5 kg

Environment

NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529 (enclosures with single door)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	61.0 cm
Package 1 Length	61.5 cm
Package 1 Weight	15.5 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	18
Package 2 Height	199.5 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	292.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)