

# Product datasheet

Specifications



## Vigi iC60 - earth leakage add-on block - 1P + N - 63A - 300mA - A type

Local distributor code:

396735021

A9V06663

EAN Code: 3606480551819

### Main

Range	Acti9
product or component type	Add-on residual current devices
Device short name	Vigi iC60
poles description	1P + N
Neutral position	Left
[In] rated current	63 A
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Earth leakage protection type	Type A
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	230...240 V AC 50/60 Hz conforming to EN/IEC 61009-1 230...240 V AC 50/60 Hz conforming to EN/IEC 61009-2-1
Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
9 mm pitches	4

### Complementary

Device location in system	Outgoer
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Range compatibility	Acti 9 Acti9 iC60
Product compatibility	Single terminal
Local signalling	Trip indicator
mounting mode	Clip-on
mounting support	DIN rail
Electrical connection to mcb	By screws
Comb busbar and distribution block compatibility	Bottom: YES
Height	91 mm
Width	54 mm
Depth	73.5 mm

<b>net weight</b>	0.165 kg
<b>Connections - terminals</b>	Tunnel type terminal downside for 1 cable(s) 1...35 mm <sup>2</sup> rigid without cable end Tunnel type terminal downside for 1 cable(s) 1...25 mm <sup>2</sup> flexible without cable end Tunnel type terminal downside for 1 cable(s) 1...25 mm <sup>2</sup> flexible with cable end
<b>Wire stripping length</b>	14 mm for bottom connection
<b>Tightening torque</b>	3.5 N.m bottom

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
<b>Pollution degree</b>	3 conforming to IEC 60947-2
<b>Electromagnetic compatibility</b>	8/20 µs impulse withstand, 250 A conforming to IEC 61009-1
<b>ambient air temperature for operation</b>	-25...60 °C
<b>ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.500 cm
<b>Package 1 Width</b>	11.300 cm
<b>Package 1 Length</b>	14.500 cm
<b>Package 1 Weight</b>	216.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	15
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	3.682 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Plastic Parts Product

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile** No need of specific recycling operations