

Weidmüller Interface GmbH & Co. KG

SAK 2.5/35

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







To feed through power, signal, and data is the classical requirement in electrical engineering and panel building. The insulating material, the connection system and the design of the terminal blocks are the differentiating features. A feed-through terminal block is suitable for joining and/or connecting one or more conductors. They could have one or more connection levels that are on the same potential or insulated against one another.

Feed-through terminal block, Screw connection, beige / yellow, 2.5 mm², 24 A, 800 V, Number of connections: 2, Number of levels: 1, TS 35, V-2, PA 66, 100 °C
0380460000
SAK 2.5/35
4008190042363
100 pc(s).
1020000000



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dim	ensions	and	weights
	GIISIUIIS	anu	WEIGHT

Depth	40 mm	Depth (inches)	1.575 inch
Height	44.5 mm	Height (inches)	1.752 inch
Width	6.1 mm	Width (inches)	0.24 inch
Net weight	6.33 g		

Temperatures

Storage temperature	-25 °C55 °C	Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C

Material data

Material	PA 66	Colour	beige / yellow
UL 94 flammability rating	V-2		

Rating data IECEx/ATEX

Certificate No. (ATEX)	TUEV18ATEX8207U	Certificate No. (IECEX)	IECEXTUR18.0017U
Max. voltage (ATEX)	690 V	Current (ATEX)	24 A
Wire cross section max. (ATEX)	6 mm²	Max. voltage (IECEX)	690 V
Current (IECEX)	24 A	Wire cross section max. (IECEX)	6 mm²
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certifi- cate of Conformity	Marking EN 60079-7	Ex eb II C Gb
Ex 2014/34/EU label	II 2 G D		

System specifications

Version	Screw connection, for scre- wable cross-connection, One end without connec-	End cover plate required	
	tor		Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35	N-function	No
PE function	No	PEN function	No

Additional technical data

Explosion-tested version	Yes	Installation advice	Direct mounting
Number of similar terminals	1	Open sides	right
Type of mounting	Snap-on		

CSA rating data

Certificate No. (CSA)	12400-129	Current size C (CSA)	25 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	10 AWG
Wire cross section min. (CSA)	26 AWG		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conductors for clamping (additional connection)

Conductor cross-section, flexible plu	s	Connection type, additional connection
plastic collar DIN 46228/1, further	con-	<i>''</i>
nection, max.	4 mm ²	Screw connection

Conductors for clamping (rated connection)

Blade size	0.6 x 3.5 mm	Clamping range, max.	6 mm ²
Clamping range, min.	0.13 mm ²	Clamping screw	M 2.5
Connection cross-section, stranded,		Connection cross-section, stranded, mi	n.
max.	4 mm ²		0.5 mm ²
Connection direction	on side	Gauge to IEC 60947-1	A3
Number of connections	2	Stripping length	10 mm
Tightening torque, max.	0.8 Nm	Tightening torque, min.	0.4 Nm
Torque level with DMS electric screw-		Twin wire-end ferrules, max.	
driver	1		1.5 mm ²
Twin wire-end ferrules, min.	0.5 mm ²	Type of connection	Screw connection
Wire connection cross section AWG,		Wire connection cross section, finely	
min.	AWG 26	stranded, max.	4 mm ²
Wire connection cross section, finely		Wire connection cross-section, fine-	
stranded, min.		ly stranded with wire-end ferrules DIN	
	0.5 mm ²	46228/1, max.	4 mm ²
Wire connection cross-section, fine-		Wire connection cross-section, fine-	
ly stranded with wire-end ferrules DIN		ly stranded with wire-end ferrules DIN	
46228/1, min.	0.5 mm ²	46228/4, max.	4 mm ²
Wire connection cross-section, fine-		Wire connection cross-section, solid	
ly stranded with wire-end ferrules DIN		core, max.	
46228/4, min.	0.5 mm ²		6 mm ²
Wire connection cross-section, solid	<u> </u>		
core, min.	0.5 mm ²		

General

Installation advice	Direct mounting	Rail	TS 35
Standards		Wire connection cross	section AWG,
	IEC 60947-7-1	min.	AWG 26

Rating data

Rated cross-section	2.5 mm ²	Rated voltage	800 V
Rated DC voltage	800 V	Rated current	24 A
Current at maximum wires	41 A	Standards	IEC 60947-7-1
Volume resistance according to IE	C	Rated impulse withstand vo	oltage
60947-7-x	1.33 mΩ		8 kV
Power loss in accordance with IEC		Pollution severity	
60947-7-x	0.77 W		3

UL rating data

Certificate No. (UR)	E60693	Conductor size Factory wiring max. (UR)	12 AWG
Conductor size Factory wiring min. (UR)	22 AWG	Conductor size Field wiring max. (UR)	12 AWG
Conductor size Field wiring min. (UR)	22 AWG	Current size C (UR)	20 A
Voltage size C (UR)	600 V		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897	ETIM 9.0	EC000897
ECLASS 9.0	27-14-11-20	ECLASS 9.1	27-14-11-20
ECLASS 10.0	27-14-11-20	ECLASS 11.0	27-14-11-20
ECLASS 12.0	27-14-11-20	ECLASS 13.0	27-25-01-01
ECLASS 14.0	27-25-01-01		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate No. (UR)	E60693

Downloads

Approval/Certificate/Document of Con-	Attestation of Conformity
formity	<u>CFAT SAK 2.5/35</u>
	UKCA Ex Attestation of Conformity
	<u>CB Certificate</u>
	CB Test Certificate
	<u>Lloyds Register Certificate</u>
	IECEx Certificate
	ATEX Certificate
	DNV Certificate
	Declaration of Conformity
	UKCA declaration of conformity
Engineering Data	<u>CAD data – 22364_SAK_2.5-35_DXF.dxf</u>
	CAD data – STEP
Product Change Notification	20210308 Technical Change SAK PA 35
User Documentation	<u>StorageConditionsTerminalBlocks</u>
	NTI SAK 2.5/35
Catalogues	Catalogues in PDF-format



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

SAK-Series



A partition plate is used for the optical separation of circuits or used for electrical isolation from neighbouring cross-connectors. In contrast to the end plate, the contour can be larger than the adjacent terminal blocks. However, it should not be smaller, as otherwise the required clearance and creepage distances within the application can no longer be maintained.

General ordering data

Туре	TSCH 1	Version
Order No.	0319160000	Small partition (terminal), PA 66, beige, Continuous operating temp.,
GTIN (EAN)	4008190097219	max.: 100 °C
Qty.	100 pc(s).	
Туре	TW SAK2.5	Version
Order No.	0302860000	Partition plate (terminal), beige, Height: 50 mm, Width: 1.5 mm, V-2,
GTIN (EAN)	4008190032968	PA 66
Qty.	20 pc(s).	
Туре	TW SAK2.5 BL	Version
Order No.	0302880000	Partition plate (terminal), blue, Height: 50 mm, Width: 1.5 mm, V-2, PA
GTIN (EAN)	4008190047948	66
Qty.	20 pc(s).	

SAK-Series



Warning covers with a flash symbol provide more safety for man and machine. They are used where external voltage must be indicated within the application.

Туре	AD 3 SAK2.5	Version
Order No.	0297900000	Terminal cover, yellow, PVC, Height: 24 mm, Width: 18 mm, Depth: 1
GTIN (EAN)	4008190038229	mm, V-2
Qty.	50 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6 MC SDR	Version
Order No.	1609830000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190456603	Weidmueller, To customer specification
Qty.	200 pc(s).	
Туре	DEK 5/6 PLUS MC SDR	Version
Type Order No.	DEK 5/6 PLUS MC SDR 1038650000	Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
• •	·	

Testsockets



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

Type STB 8.5/5/2.3/M3 SAK2.5 Version
Order No. 0280600000 Accessories, Socket
GTIN (EAN) 4008190023188
Otty. 50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

ype DEK 5/6 PLUS MC NE WS Vers

Order No. 1011320000 Dekafix, Term

GTIN (EAN) 4032248717644 Weidmueller, white

Qty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/6 MC NE BR Version

Order No. 1454900000 Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

GTIN (EAN) 4050118323313 Weidmueller, brown

Qty. 1,000 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

DEIX E (C. MO NE MO	V ·
, , , , , , , , , , , , , , , , , , , ,	Version
1609820000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
4008190203436	Weidmueller, white
1,000 pc(s).	
DEK 5/6 MC NE BL	Version
1238290000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
4050118267327	Weidmueller, blue
1,000 pc(s).	
DEK 5/6 MC NE GN	Version
1238310000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
4050118271812	Weidmueller, green
1,000 pc(s).	
DEK 5/6 MC NE GR	Version
1238330000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
4050118323306	Weidmueller, grey
1,000 pc(s).	
DEK 5/6 MC NE GE	Version
1238280000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
4050118038750	Weidmueller, yellow
1,000 pc(s).	
DEK 5/6 MC NE OR	Version
<u>1912090000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
4032248540525	Weidmueller, orange
1,000 pc(s).	
	1,000 pc(s). DEK 5/6 MC NE BL 1238290000 4050118267327 1,000 pc(s). DEK 5/6 MC NE GN 1238310000 4050118271812 1,000 pc(s). DEK 5/6 MC NE GR 1238330000 4050118323306 1,000 pc(s). DEK 5/6 MC NE GE 1238280000 4050118038750 1,000 pc(s). DEK 5/6 MC NE OR 1912090000 4032248540525

Screws



Depending on the terminal block or also accessories, we offer different types of screws as additional items or also spare parts.

Туре	BFSC M3X22 PA/RT	Version
Order No.	0128900000	Mounting screw (Terminal), 3.00 mm, Polyamide 66, Depth: 4.8 mm,
GTIN (EAN)	4008190084158	Width: 4.8 mm, Height: 22 mm
Qty.	100 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Q/SAK



Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

Туре	Q 3 SAK2.5	Version
Order No.	0337100000	Cross-connector (terminal), when screwed in, grey, 24 A, Number of
GTIN (EAN)	4008190015411	poles: 3, Pitch in mm (P): 6.00, Insulated: No, Width: 17.2 mm
Qty.	50 pc(s).	
Туре	Q 4 SAK2.5	Version
Order No.	0337200000	Cross-connector (terminal), when screwed in, grey, 24 A, Number of
GTIN (EAN)	4008190142902	poles: 4, Pitch in mm (P): 6.00, Insulated: No, Width: 23.4 mm
Qty.	50 pc(s).	
Туре	Q 10 SAK2.5	Version
Order No.	0368700000	Cross-connector (terminal), when screwed in, grey, 24 A, Number of
GTIN (EAN)	4008190107796	poles: 10, Pitch in mm (P): 6.00, Insulated: No, Width: 60.6 mm
Qty.	20 pc(s).	
Туре	Q 2 SAK2.5	Version
Order No.	0337000000	Cross-connector (terminal), when screwed in, grey, 24 A, Number of
GTIN (EAN)	4008190005801	poles: 2, Pitch in mm (P): 6.00, Insulated: No, Width: 11.5 mm
Qty.	50 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

DEK 5/6



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Тур	ре	DEK 5/6 MM WS	Version
Ore	der No.	2007120000	Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white
GT	IN (EAN)	4050118392104	
Qt	y.	600 pc(s).	

Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon[®] Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

Туре	BZT 1 WS 10/5	Version
Order No.	1805490000	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 pc(s).	
Туре	BZT 1 ZA WS 10/5	Version
Type Order No.	BZT 1 ZA WS 10/5 1805520000	Version Accessories, Marker holder
	,	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

SAK-Series



End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

General ordering data

Туре	AP SAK2.5+AST3+4/35	Version
Order No.	0460560000	End plate (terminals), beige, Height: 39 mm, Width: 1.5 mm, V-2, PA
GTIN (EAN)	4008190048334	66
Qty.	20 pc(s).	
Туре	AP SAK2.5+AST3+4/35 BL	Version
Type Order No.	AP SAK2.5+AST3+4/35 BL 0460580000	Version End plate (terminals), blue, Height: 39 mm, Width: 1.5 mm, V-2, PA 66
	· ·	

Test plugs



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

Туре	PS 2.3 RT	Version		
Order No.	0180400000	Test adapter (terminal), 230 V, 20 mA		
GTIN (EAN)	4008190060121			
Qty.	20 pc(s).			