Product datasheet

Specifications

Transparent boot for circular flush push button Ø22

Local distributor code:
393612529   ZBPA

EAN Code: 3389110355505

Main

Range of product	Harmony XB4 Harmony XB5
Accessory / separate part type	Single boot
Product or component type	Transparent boot
Accessory / separate part category	Protection accessories
Accessory / separate part destination	Flush push-button
Shape	Round
Quantity per set	Set of 10

Complementary

Colour	Transparent
Product weight	0.002 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	3.000 cm
Package 1 Length	3.000 cm
Package 1 Weight	2.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.200 cm
Package 2 Width	7.200 cm
Package 2 Length	9.000 cm
Package 2 Weight	40.800 g
Unit Type of Package 3	S03
Number of Units in Package 3	400
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	2.080 kg

Logistical informations

Country of origin   FR

Contractual warranty

Warranty   18 months

Life Is On | Schneider Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ›

How we assess product sustainability ›

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	**1**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
China RoHS Regulation	**China RoHS declaration**

Use Again

Repack and remanufacture

Take-back	**No**

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Harmony XB4

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws

Operating temperature from -40°C –to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Offer Marketing Illustration

Product benefits / Features

Image of product / Alternate images

Alternative