

"PanelSeT S3D seismic plain door with mount.plate - H800xW600xD300 - IP65 - IK10"

Local distributor code:

402657857 NSYS3D6G8630P

EAN Code: 3606480793981

Main

| Range | PanelSeT | |
|----------------------------|--|--|
| product name | S3D 6G | |
| Enclosure application | Seismic | |
| Product or component type | Enclosure | |
| Enclosure nominal height | 800 mm | |
| Enclosure nominal width | 600 mm | |
| Enclosure nominal depth | 300 mm | |
| Door type | Plain | |
| Mounting plate description | Reinforce | |
| Enclosure mounting | Wall mounted | |
| Device composition | 1 x body 1 x door 1 x lock 2 x fixing bracket 1 x mounting plate 1 x earthing components door and lock 1 x cable gland plate | |
| Continuity of earth | Earthing connection between body and door | |

Complementary

| Body type | Single piece body Gutter-shaped front rail | |
|-----------------------------|---|--|
| Number of doors | Front face: 1 door(s) | |
| Door opening side | Right (120 °) | |
| Lock type | 3-point closure | |
| Type of keylock | 405E | |
| Type of operating handle | Swing handle | |
| Accessibility for operation | Front | |
| Removable parts | Cable gland plate by screws | |
| Material | Steel | |
| Thickness | Body: 2 mm Door: 2 mm Cable gland plate: 1.5 mm | |
| Surface finish | Epoxy-polyester powder | |
| Colour | Grey (RAL 7035) | |
| Net weight | 47 kg | |

Environment

| Surface treatment | 87 % decontaminable painting conforming to NF T 30-501. | |
|-------------------------|---|--|
| Standards | IEC 62208 EDF CRT 91 C 112 00 | |
| IP degree of protection | IP65 conforming to IEC 60529 | |
| IK degree of protection | IK10 conforming to IEC 62262 | |
| Seismic performance | Seismic tests 6G conforming to EDF CRT 91 C 112 00 | |

Packing Units

| • | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 35.000 cm |
| Package 1 Width | 62.000 cm |
| Package 1 Length | 88.000 cm |
| Package 1 Weight | 36.800 kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 189.000 cm |
| Package 2 Width | 100.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 306.400 kg |

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 347 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Packaging made with recycled cardboard | No |
|--|--------------------------------------|
| Packaging without single use plastic | No |
| SCIP Number | Ba0ee14c-eebb-47d8-a070-ade906247bb0 |
| China RoHS Regulation | China RoHS declaration |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |