

wall-mounting encl. polyester monobloc IP66 530x430x200mm 3p.lock glazed door

Local distributor code:

403422722 NSYPLM54TVG

EAN Code: 3606480776618

Main

Range	Thalassa
product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	530 mm
Nominal width	430 mm
Nominal depth	200 mm
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 1 handle lock
Door type	Transparent
Lock type	3 points lock, handle with 1242E key lock

Complementary

Number of locks	1	
Mounting plate description	Without mounting plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Body: polyester reinforced with fibreglass Door: tempered glass	
Colour	Grey (RAL 7035)	
Electrical insulation class	Class II	

Environment

IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK08 conforming to IEC 62262	
Fire resistance	960 °C conforming to IEC 62208	
Ambient air temperature for operation	-4080 °C	

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	45.0 cm
Package 1 Width	23.0 cm
Package 1 Length	56.0 cm
Package 1 Weight	9.003 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	30
Package 2 Height	120 cm
Package 2 Width	100 cm
Package 2 Length	193 cm
Package 2 Weight	285 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	70
Environmental Disclosure	Product Environmental Profile

Use Better

Minimum percentage of recycled plastic content	37	
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No