


## Data Sheet

### Pg Nickel Plated IP68 Cable Glands – Standard Thread



**Material:** Nickel Plated Brass

**Claw:** PA

**Sealing and sealing ring:** NBR

**Approvals:** CE, RoHS, REACH

**Protection degree:** IP68

**Temperature resistance:** -40°C to 100°C, short time to 120°C

| Part Number | Cable Range (mm) | Thread O.D. AG (Pg) | Mounting Hole Diameter (mm) | Thread Length GL (mm) | Joint Length H (mm) | Spanner Size (mm) |
|-------------|------------------|---------------------|-----------------------------|-----------------------|---------------------|-------------------|
| IP68PG7/NP  | 3-6.5            | 7                   | 12.5-12.7                   | 7                     | 19                  | 14                |
| IP68PG9/NP  | 4-8.0            | 9                   | 15.2-15.4                   | 8                     | 20                  | 17                |
| IP68PG11/NP | 5-10.0           | 11                  | 18.6-18.8                   | 8                     | 21                  | 20/21             |
| IP68PG13/NP | 6-12.0           | 13.5                | 20.4-20.6                   | 8                     | 22                  | 22                |
| IP68PG16/NP | 10-14.0          | 16                  | 22.5-22.7                   | 9                     | 23                  | 24                |
| IP68PG21/NP | 13-18.0          | 21                  | 28.3-28.5                   | 9                     | 27                  | 30                |
| IP68PG29/NP | 18-25.0          | 29                  | 37-37.2                     | 11                    | 31                  | 40                |
| IP68PG36/NP | 22-32.0          | 36                  | 47-47.2                     | 12                    | 37                  | 50                |
| IP68PG42/NP | 30-38.0          | 42                  | 54-54.2                     | 13                    | 38                  | 57                |