




PRODUCT-DETAILS

XT5D 400 4p F F

XT5D 400 4p F F



General Information	
Extended Product Type	XT5D 400 4p F F
Product ID	1SDA100548R1
EAN	8056221006248
Catalog Description	XT5D 400 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT5D 400 FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group	UL 2799 Zero Waste To Landfill Validation available
Waste To Landfill Target	
End Of Life	9AKK108468A2353
Disassembling	
Instructions	
Environmental Product	9AKK108468A9746
Declaration - EPD	9AKK108468A1893
Recyclability Rate of the	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Product acc. to EN45555	

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	3d18b1f4-4d08-4643-b3a9-f7162aec4b52 Italy
Simplified SCIP	515fae19-d5a1-4c9d-bfd5-7150013e78dc France f9fcc9e8-e30d-4774-ba61-0f244abb42a7 Greece 38d310c0-63d4-4423-9a8d-799701e9ca16 Germany 60ce7c87-9c46-4138-a2c3-1753a7ef888e Finland b77336b9-c285-4ec0-8eae-329474e23b67 Hungary 63601c75-41ed-4206-80a2-7de275c81b81 Netherlands 0a555105-8471-4a70-af4c-8b07c080eba2 Sweden 71e0c04e-df95-48f8-801f-e507c7e0619a Germany 015b7f0b-579a-4f74-ad7a-f1dd6bee7108 Portugal f38f9f6c-2841-48ff-a64b-ccfc16d80025 Germany 91ee2f17-828a-4814-94a3-bc834f0ad9bc Poland 015b7f0b-579a-4f74-ad7a-f1dd6bee7108 Portugal f9fcc9e8-e30d-4774-ba61-0f244abb42a7 Greece a9445c33-1800-49bd-ad8f-ddbfac187b18 Germany 84f1e865-66ae-4e00-a5ed-44780ad5ea77 Poland f38f9f6c-2841-48ff-a64b-ccfc16d80025 Germany 71e0c04e-df95-48f8-801f-e507c7e0619a Germany e136e2ce-35f6-456f-afb9-2c2388c709ab Spain aae2e110-77ea-4db8-977b-3bc59204476d France f19452ee-00f8-448d-b689-7cc7915a2713 Hungary b77336b9-c285-4ec0-8eae-329474e23b67 Hungary 61217bed-bf27-4dce-91e9-e73db4756400 Estonia aae2e110-77ea-4db8-977b-3bc59204476d France 91ee2f17-828a-4814-94a3-bc834f0ad9bc Poland f19452ee-00f8-448d-b689-7cc7915a2713 Hungary c4b6826b-b6bf-4324-9e05-0f2a9ece7770 Croatia ec7e07d3-f738-4f6d-a734-bec5320ab392 Czech Republic 63601c75-41ed-4206-80a2-7de275c81b81 Netherlands c17f2616-f7a6-4bcb-99bc-80d9a985600e Bulgaria 515fae19-d5a1-4c9d-bfd5-7150013e78dc France 01bac6da-cdc9-40cb-a0e7-8a534c2bbe67 Sweden aa3e606e-eb21-4e5b-9b99-47c77fc221dd Poland 0a555105-8471-4a70-af4c-8b07c080eba2 Sweden e136e2ce-35f6-456f-afb9-2c2388c709ab Spain 34ca218e-e643-435f-8571-3b099d355aba Belgium 61217bed-bf27-4dce-91e9-e73db4756400 Estonia 0746af35-681d-4bc2-b5ec-4609e3a0eaa2 Belgium 60ce7c87-9c46-4138-a2c3-1753a7ef888e Finland 38d310c0-63d4-4423-9a8d-799701e9ca16 Germany f2d07ccb-a874-4b5f-ba1e-270431a75952 Germany 01bac6da-cdc9-40cb-a0e7-8a534c2bbe67 Sweden a9445c33-1800-49bd-ad8f-ddbfac187b18 Germany ec7e07d3-f738-4f6d-a734-bec5320ab392 Czech Republic aa3e606e-eb21-4e5b-9b99-47c77fc221dd Poland 34ca218e-e643-435f-8571-3b099d355aba Belgium 1f9ccb0e-bbd8-4434-98fe-32035a458f6d Norway 0746af35-681d-4bc2-b5ec-4609e3a0eaa2 Belgium f2d07ccb-a874-4b5f-ba1e-270431a75952 Germany b9837d3d-eb64-4f6d-97db-ee272ad708b0 Denmark c17f2616-f7a6-4bcb-99bc-80d9a985600e Bulgaria b9837d3d-eb64-4f6d-97db-ee272ad708b0 Denmark 84f1e865-66ae-4e00-a5ed-44780ad5ea77 Poland 1f9ccb0e-bbd8-4434-98fe-32035a458f6d Norway c4b6826b-b6bf-4324-9e05-0f2a9ece7770 Croatia

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT5DE440ADFF000XXX
E-Number (Norway)	4380446
EAN	8056221006248
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.6 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.088 kg
Package Level 1 EAN	8056221006248

Additional Information

Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Version	F
CAD Dimensional Drawing	1SDH002065A1183 1SDH002065A1131

Technical

Electrical Durability	7000 cycle 60 cycles per hour
Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4P
Order Multiple	1 piece
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage	1000 V

(U _i)	
Rated Operational Current AC-23A (I _e)	(400 V) 400 A (690 V) 400 A
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw})	5 kA
Rated Uninterrupted Current (I _u)	400 A
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

External Classifications and Standards

ETIM 9	EC000216 - Switch disconnecter (low voltage)
ETIM 10	EC000216 - Switch disconnecter (AC)
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

