



PRODUCT-DETAILS

# E1.2B 1250 Ekip Touch LSI 4p F F

## E1.2B 1250 Ekip Touch LSI 4p F F



| General Information   |                                                                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E1.2B 1250 Ekip Touch LSI 4p F F                                                                                                                                                                |
| Product ID            | 1SDA071455R1                                                                                                                                                                                    |
| EAN                   | 8015644753054                                                                                                                                                                                   |
| Catalog Description   | E1.2B 1250 Ekip Touch LSI 4p F F                                                                                                                                                                |
| Long Description      | C.BREAKER SACE EMAX2 E1.2B 1250 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

| ABB EcoSolutions                                |                                                               |
|-------------------------------------------------|---------------------------------------------------------------|
| ABB EcoSolutions                                | Yes                                                           |
| ABB Site Meeting Group Waste To Landfill Target | UL 2799 Zero Waste To Landfill Validation available           |
| End Of Life Disassembling Instructions          | 9AKK108468A2360                                               |
| Environmental Product Declaration - EPD         | 9AKK108468A1900<br>9AKK108468A3028                            |
| Recyclability Rate of the                       | Design for Closing Resource Loops - Standard EN45555 - 76.4 % |

Product acc. to EN45555

Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| REACH Declaration                           | 9AKK108466A1425                                                        |
| RoHS Information                            | 9AKK108466A1424                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326                                                        |

Environmental

|                           |                 |
|---------------------------|-----------------|
| Environmental Information | 9AKK108467A6707 |
|---------------------------|-----------------|

Ordering

|                          |                      |
|--------------------------|----------------------|
| Order Code US and Canada | ZABREHBE000A000000XX |
| EAN                      | 8015644753054        |
| Minimum Order Quantity   | 1 piece              |
| Customs Tariff Number    | 85362090             |

Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 280 mm |
| Product Net Height         | 296 mm |
| Product Net Depth / Length | 183 mm |
| Product Net Weight         | 16 kg  |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 350 mm        |
| Package Level 1 Height         | 350 mm        |
| Package Level 1 Depth / Length | 330 mm        |
| Package Level 1 Gross Weight   | 18 kg         |
| Package Level 1 EAN            | 8015644753054 |

Additional Information

|                         |                     |
|-------------------------|---------------------|
| Product Main Type       | SACE Emax 2         |
| Product Name            | Air Circuit Breaker |
| Product Type            | Air Circuit Breaker |
| Version                 | F                   |
| CAD Dimensional Drawing | 1SDH001252R0042     |

## Technical

|                                                                                           |                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Current Type                                                                              | AC                                                                                                                                                                               |
| Electrical Durability                                                                     | Ue = < 440 V 8000 cycle<br>Ue = 500 ... 690 V 6500 cycle<br>30 cycles per hour                                                                                                   |
| Mechanical Durability                                                                     | 20000 cycle<br>60 cycles per hour                                                                                                                                                |
| Neutral Pole Current ([% I <sub>n</sub> ])                                                | 100 %                                                                                                                                                                            |
| Number of Poles                                                                           | 4P                                                                                                                                                                               |
| Power Loss                                                                                | 122 W                                                                                                                                                                            |
| Rated Current (I <sub>n</sub> )                                                           | 1250 A                                                                                                                                                                           |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )                                       | acc. to IEC 60947-2 12 kV                                                                                                                                                        |
| Rated Insulation Voltage (U <sub>i</sub> )                                                | AC 1000 V                                                                                                                                                                        |
| Rated Operational Voltage                                                                 | 690 V AC                                                                                                                                                                         |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )                          | (220 V AC) 42 kA<br>(230 V AC) 42 kA<br>(380 V AC) 42 kA<br>(400 V AC) 42 kA<br>(415 V AC) 42 kA<br>(440 V AC) 42 kA<br>(500 V AC) 42 kA<br>(660 V AC) 42 kA<br>(690 V AC) 42 kA |
| Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cu</sub> (I <sub>cs</sub> ) | 100 %                                                                                                                                                                            |
| Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )                         | for 1 s 42 kA<br>for 3 s 24 kA                                                                                                                                                   |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )                         | (400 V AC) 42 kA<br>(415 V AC) 42 kA<br>(440 V AC) 42 kA<br>(500 V AC) 42 kA<br>(525 V AC) 42 kA<br>(690 V AC) 42 kA                                                             |
| Rated Uninterrupted Current (I <sub>u</sub> )                                             | 1250 A                                                                                                                                                                           |
| Rated Voltage (U <sub>r</sub> )                                                           | 690 V                                                                                                                                                                            |
| Recommended Screw Driver                                                                  | Main Circuit M10                                                                                                                                                                 |
| Release                                                                                   | Ekip Touch LSI                                                                                                                                                                   |
| Release Type                                                                              | EL                                                                                                                                                                               |
| Short-Circuit Performance Level                                                           | B                                                                                                                                                                                |
| Standards                                                                                 | IEC                                                                                                                                                                              |
| Sub-type                                                                                  | E1.2                                                                                                                                                                             |
| Suitable for IT Networks                                                                  | Yes, 690V                                                                                                                                                                        |
| Terminal Connection Type                                                                  | Front                                                                                                                                                                            |
| Terminal Type                                                                             | Bolt                                                                                                                                                                             |
| Tightening Torque                                                                         | 45 N·m                                                                                                                                                                           |

## Certificates and Declarations

|                                   |                         |
|-----------------------------------|-------------------------|
| ATEX Certificate                  | No certification needed |
| CSA Certificate                   | No certification needed |
| CSA Certificate (Intrinsic Safe)  | No certification needed |
| Data Sheet, Technical Information | 1SDC200023D0209         |
| Declaration of Conformity - CE    | 9AKK106713A5546         |
| UL Certificate                    | No certification needed |
| VDE Certificate                   | No certification needed |
| Mechanical Drawings               | 1SDH000999R0101         |
| Wiring Diagram                    | 1SDM000091R0001         |
| Instructions and Manuals          | 1SDH000999R0002         |
| Instructions and Manuals (Part 2) | 1SDH001316R1002         |

## External Classifications and Standards

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 10                            | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers                                                 |
| Object Classification Code         | Q                                                                            |
| UNSPSC                             | 39121615                                                                     |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                             | V11.1 : 27370409                                                             |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

