### Product Data Sheet



## Polyester Cabinet 600x500x230

### Polyester Cabinet



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Protection class	IP66
Glow wire test	850 °C
Temp. range min	-25 °C
Temp. range max	85 °C
Impact resistance	IK10
Material	Polyester
Product Color	RAL 7035
External dimensions LxWxH	600x500x230mm
Туре	Polyester Cabinet 600x500x230
Order no. UK	50108497
Packing unit	1

#### Additional Info:

- Empty cabinets made of polyester reinforced with fiberglass
- For use in electrical networks
- For surface mounting
- Insulation: Class II
- With lock
- Optional locks: metal key, triangle, padlock
- Door opening: 180°
- Option to put mounting plate in the enclosure (insulating or metallic)
- External fixing to the wall
- Resistant to chemical and atmospheric agents

Specification to the following:

Directive 2014/35/UE

Directive 2011/65/UE (RoHS)

Your Contact:

#### WISKA UK Ltd.

info@wiska.co.uk · www.wiska.co.uk





# Electrical Low Voltage Regulation In Accordance with EN 62208 and EN 60670-1

#### Recommended accessories

Polyester Plate for 600x500x230mm	50108722
Metal Plate for 600x500x230mm	50108727

13.05.2025