

Junction box

Abox 025-L/sw



Abox 025-L/sw

Junction box

CUSTOMIZABLE

Productnumber: 80200001

Dimensions: 87 x 87 x 52 mm

Junction box, protection class IP66, nominal cross-section 2.5 mm², certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), DLG (Ammonia resistance), self-sealing, soft insertion membranes, M16/M20, sealing range 4 - 16 mm, (1 rear, 8 side), internal fixing points, for standard indoor and protected outdoor installations

black, Ui=1000 V AC, without terminals



Technical Data

electrical characteristics

Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1000 V
Max. conductor cross section:	2,5 mm²
Protection class:	II
Type of protection:	IP66
Terminal type:	none

Colours

Base unit colour:	black
Cover colour:	black

Dimensions

Width:	87 mm
Length:	87 mm
Height:	52 mm
Inner length:	75 mm
Inner width:	75 mm
Inner height:	37 mm
Weight:	0.098 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	750 °C

Max. number of terminals per cross section acc. to DIN VDE 0606-1

max. amount of terminals at 1,5²:	8
max. amount of terminals at 2,5²:	6

Max. number of wires per cross section acc. to DIN VDE 0606-1

max. amount of wires at 1,5²:	24
max. amount of wires at 2,5²:	20

mechanical properties

for sealing range min:	4 mm
for sealing range max:	16 mm
Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1.2 Nm
Type of fastening:	Wall/ceiling mounting
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	55 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902663422
ETIM Class:	EC002600
Custom tariff number:	85389099

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene
Entry material:	Thermoplastic elastomer
Sealing material:	Thermoplastic elastomer
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
Test mark:	DLG (Ammonia resistance)

Accessories

- [22701601 - KVR M16-MGM/sw - Cable gland](#)
- [22702001 - KVR M20-MGM/sw - Cable gland](#)
- [22702101 - KVR M20-GDB/MGM/sw - Cable gland](#)
- [26001601 - DMS M16/sw - Double-membrane seals](#)
- [26002001 - DMS M20/sw - Double-membrane seals](#)
- [89610001 - KKA 1515/sw - Cable duct adapter](#)
- [89500101 - Abox PST 025-100 - Sealing kit](#)
- [89520201 - Abox 025 TS15 - Standard rail](#)
- [89600201 - Abox 025/040 KH 2273 2,5² - Terminal holder](#)
- [89600301 - Abox 025/040 KH 221 4² - Terminal holder](#)
- [89640401 - Abox 025/040 KLS-2,5²/4² - Terminal block](#)
- [89601001 - MABF 65-1 - Mast/pipe fixing set](#)

Cable gland

