



Color: ☐ transparent                      Similar to illustration

Physical data	
Width	15.2 mm / 0.598 inches

Material data	
Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	transparent
Material group	IIIa
Insulation material (main housing)	Polycarbonate (PC)
Flammability class per UL94	V2
Fire load	0.065 MJ
Weight	1.1 g

Environmental requirements	
Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data	
Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	50 (10) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332283182
Customs tariff number	39269097900



Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 282-882



↓

Documentation				
Bid Text				
282-882	19.02.2019	xml 2.57 KB	↓	
282-882	03.03.2017	doc 23.50 KB	↓	

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 282-882	EPLAN Data Portal 282-882
↓	↓
	WSCAD Universe 282-882
	↓
	ZUKEN Portal 282-882
	↓

Installation Notes

Locking system



Snapping transparent locking cover onto 1–8 disconnect links:  
a) Mechanically lock several links for multi-pole switching applications  
b) Protect markers

Snapping transparent locking cover onto 1–8 disconnect links:  
a) Mechanically lock several links for multi-pole switching applications  
b) Protect markers

