

TeSys Vario - emergency stop switch disconnector - 63 A - on door

VCF3

Local distributor code: 23065776

EAN Code: 3389110165999

Main

Range	TeSys	
Product Name	TeSys VARIO	
Device Short Name	VCF	
Product Type	Emergency stop switch disconnector	

Complementary

Complementary	
Device Composition	Switch
	Handle
Mounting Support	Handle: door
	Switch: door
Mounting Method	By 4 screws for handle
Performance Level	High performance
Number of Poles	3P
Contact Type and Composition	3 NO
[Ue] IEC Rated Operational Voltage	690 V AC 50/60 Hz
IEC Rated Operational Power in W	11 kW at 230240 V (AC-3)
	22 kW at 500 V (AC-3)
	22 kW at 690 V (AC-23A)
	30 kW at 500 V (AC-23A)
	18.5 kW at 400415 V (AC-3)
	18.5 kW at 690 V (AC-3)
	15 kW at 230240 V (AC-23A)
	22 kW at 400415 V (AC-23A)
[le] Rated Operational Current	41.5 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	63 A
[Ithe] Conventional Enclosed Thermal Current	50 A
Making Capacity (I Rms)	630 A at 400 V AC-21A
	630 A at 400 V AC-22A
	630 A at 400 V AC-23A
Breaking Capacity	500 A at 400 V (AC-21A)
	500 A at 400 V (AC-22A)
	500 A at 400 V (AC-23A)
Rated Conditional Short Circuit	10 kA at 400 V - associated fuse 63 A aM
Current	10 kA at 400 V - associated fuse 63 A gG
[Icm] Rated Short Circuit Making Capacity	2.1 kA at 400 V at Ipeak
[Icw] Rated Short Time Withstand Current	756 A at 400 V duration: 1 s
[Uimp] Rated Impulse Withstand Voltage	8 kV

Suitability for Isolation	Yes	
Network Type	DC AC	
Intermittent Duty Class	30	
Control Type	Rotary handle	
Rotary Handle Mounting Style	Direct	
Handle Color	Red	
Handle Front Plate Color	Yellow	
Rotary Handle Padlocking	1 to 3 padlocks 48 mm	
Marking	0 - 1	
Mechanical Durability	30000 cycles	
Electrical Durability	30000 cycles AC-21 30000 cycles DC-15	
IEC Terminal Connection	Power circuit: screw clamp terminals25 mm² - solid Power circuit: screw clamp terminals16 mm² - flexible - with cable end	
Tightening Torque	Power circuit: 4 N.m - on screw clamp terminals	
Base Dimension	60 x 60 mm	
Height	83 mm	
Width	60 mm	
Product Weight	0.56 kg	

Environment

Standards	IEC 60947-3	
Product Certifications	GL CCC CSA UL UKCA	
Degree of Protection	IP20 conforming to IEC 60529 IP65	
Protective Treatment	TC	
Mechanical Robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27	
Ambient Air Temperature for Operation	-2050 °C	
Fire Resistance	960 °C conforming to IEC 60695-2-1	
Compatibility Code	Main switch disconnector	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.800 cm
Package 1 Width	8.500 cm
Package 1 Length	11.800 cm
Package 1 Weight	349.000 g
Unit Type of Package 2	S02

Number of Units in Package 2	12
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.422 kg
Unit Type of Package 3	P06
Number of Units in Package 3	192
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	81.060 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	34
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	63dc4fbe-3f44-4801-881b-22a3bb8008d9
REACh Regulation	REACh Declaration
PVC free	Yes

Use Again

○ Repack and remanufacture	
Recyclability potential, in %	57
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative







