

Datasheet



ENSTO CUBO S ENSTO

Mounting enclosure PC 125 x 175 x 75 mm

REF. SPCP131808T | 3443127 | EAN. 6418677155390

Size 125 x 175 x 75 mm, 50 mm base, plain sides, transparent cover, PC

> [Visit e-catalogue](#)

Main description:

Size 125 x 175 x 75 mm, 50 mm base, plain sides, transparent cover, PC

Description

Ensto Cubo S is a series of small to medium size enclosures available with knockouts or plain sides. The base of the enclosures is equipped with unique slots for printed circuit boards.

Technical characteristics

Width	125 mm	With ventilation door	No
Height	175 mm	Number of locks	0
Depth	75 mm	With cover	Yes
Material	Plastic	Transparent cover	Yes
Material quality	Other	Suitable for metrical mounting	No
Surface finishing	Untreated	Suitable for outdoor installation	Yes
Colour	Grey	Pitched roof	No
RAL-number	7035	Number of connector holes	0
Freestanding	No	Pre-stamping	No
Floor standing wall model	No	EMC-version	No
Suitable for wall mounting	No	degree of impact strength (IK)	IK08
Intermediate mounting	No	Degree of protection (IP)	IP67
Couplable	No	Degree of protection (NEMA)	6P
With mounting plate	No	Max. permitted load of the mounting plate according to IEC 62208	2 N
Mounting plate depth-adjustable	No	Enclosure capacity (Nb of modules)	0

Suitable for wall built-in	No
Pole fastening	No
With door	No
Number of doors	0
With glazed door	No

Operating / setting temperature (Min-Max)	-40-80 °C
Storage temperature (Min-Max)	-25-35 °C
Fitted with rainproof plate protection	No
Fitted with door or cover	Yes
Supplied with circuit identification labels	No

Documentation

CAD & Design specs / BIM

-  [2D_SPCP131808T_2.dxf](#) | DXF (0.45Mo)
-  [2D_SPCP131808T.dwg](#) | DWG (0.15Mo)
-  [3D_SPCP131808T_PK2_V1.STP](#) | IFC (2.88Mo)
-  [DD_SPCP131808T.pdf](#) | PDF (0.43Mo)

Agreements & certificates

-  [CE_CUBO-S_PC_2024_EN.pdf](#) | PDF (0.04Mo)
-  [LGRP-01806-V01.01-EN.pdf](#) | PDF (0.73Mo)
-  [CE_CUBO-S_PC_2024_FI.pdf](#) | PDF (0.04Mo)