

# Product datasheet

Specifications



## Floor standing encl. polyester vers.PLA compl.sealed 1000x750x320 IP65 glazed

Local distributor code:

403419654

NSYPLA1073TG

**EAN Code: 3606480774485**

## Main

Range	PanelSeT
Product name	PanelSeT PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	1000 mm
Nominal width	750 mm
Nominal depth	320 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door

## Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	1 door(s)
Door opening side	Reversible (120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	UL 508 A IEC 62208
NEMA degree of protection	NEMA 3X NEMA 3 NEMA 1 NEMA 3S NEMA 12 NEMA 13 NEMA 3R NEMA 2 NEMA 5

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Product certifications</b>	UL/cUL listed Veritas DNV Marine
<b>Electrical insulation class</b>	Class II

## Environment

<b>IP degree of protection</b>	IP65 conforming to IEC 60529 (completely sealed)
<b>IK degree of protection</b>	IK08 conforming to IEC 62262 (glazed door)
<b>Fire resistance</b>	960 °C conforming to IEC 62208
<b>Ambient air temperature for storage</b>	-35...90 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	101.000 cm
<b>Package 1 Width</b>	78.000 cm
<b>Package 1 Length</b>	37.500 cm
<b>Package 1 Weight</b>	29.600 kg
<b>Unit Type of Package 2</b>	PAM
<b>Number of Units in Package 2</b>	3
<b>Package 2 Height</b>	116.000 cm
<b>Package 2 Width</b>	100.000 cm
<b>Package 2 Length</b>	120.000 cm
<b>Package 2 Weight</b>	102.000 kg

## Logistical informations

<b>Country of origin</b>	ES
--------------------------	----

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	230 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	108 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	59 kg CO2 eq.
Carbon footprint of the installation phase [A5]	10 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	54 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1341ad4e-77b9-40e3-bab0-32043fbc5959
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	6
End of life manual availability	No need of specific recycling operations
Take-back	Nej

Technical Illustration

Dimensions

---



Image of product in real life situation

