

6A300063

Distribution industrial fuselinks BS88 Fuselink gG A3 63A 500 VAC

Strong points

- High-performance
- Increased reliability
- Safety

General characteristics

- High level performance.
- High reliability.
- Safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/6A300063>

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

Technical Characteristics

Fuse melting indicator	without striker
Fuse size	A3
Rated voltage	500 VAC
Rated current [A]	63
Type	gG

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

Commerce

Effective date	1998-03-26
Offer Life Cycle Code	40
Country of origin	HU

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	63
Rated voltage AC [V]	500
Utilization category	Other

ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

Logistics

GTIN/EAN	3596031419142
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.05
Length of the packing unit [m]	0.022
Width of the packing unit [m]	0.02
Depth of the packing unit [m]	0.085

Norms

Conformity to standards	IEC
-------------------------	-----