



Color: ■ yellow

Material data		
Note (material data)	Information on material specifications can be found here	
Color	yellow	
Material group	I	
Insulation material (main housing)	Polyamide (PA66)	
Flammability class per UL94	V0	
Fire load	0.011 MJ	
Weight	0.4 g	

Environmental requirements		
Processing temperature	-35 ... +85 °C	
Continuous operating temperature	-60 ... +105 °C	

Commercial data		
Product Group	1 (Rail Mounted Terminal Blocks)	
PU (SPU)	100 (20) pcs	
Packaging type	Box	
Country of origin	DE	
GTIN	4017332283212	
Customs tariff number	39269097900	



Product Classification	
UNSPSC	39121703
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 282-384

↓

Documentation			
Bid Text			
282-384	19.02.2019	xml 2.50 KB	↓
282-384	03.03.2017	doc 23.00 KB	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 282-384	WSCAD Universe 282-384
↓	↓
	ZUKEN Portal 282-384
	↓

Installation Notes



Lock-out snaps into one of two notched positions, preventing accidental operation of the disconnect link.