



PRODUCT-DETAILS

AUXGB-11

AUXGB-11 AUXILIARY CONTACT



General Information	
Extended Product Type:	AUXGB-11
Product ID:	1SCA162594R1001
EAN:	6417019926209
Catalog Description:	AUXGB-11 AUXILIARY CONTACT
Long Description:	OT Plus Switch disconnecter series. Auxiliary contact block for Base mounted OT16... 160G_series. 1NO and 1NC contact. Snap-on mounting on both sides of the switch. The 1NO has early break function.
Display Name:	AUXGB-11

Material Compliance	
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	1SCC011021D0201
RoHS Declaration:	1SCC011020D0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information:	9AKK108468A5537 1SCC301020C0201
Instructions and Manuals:	1SCC390188M0201
Mechanical Drawings:	AUXGB_11.stp

Environmental

Degree of Protection:	Front IP20
Pollution Degree:	3

Ordering

Minimum Order Quantity:	10 piece
Customs Tariff Number:	85389099
Country of Origin:	Bulgaria

Dimensions

Product Net Width:	16.0 mm
Product Net Height:	62.0 mm
Product Net Depth / Length:	47.6 mm
Product Net Weight:	0.027 kg

Container Information

Package Level 1 Units:	bag 10 piece
Package Level 1 Width:	165 mm
Package Level 1 Depth / Length:	70 mm
Package Level 1 Height:	16 mm
Package Level 1 Gross Weight:	0.032 kg
Package Level 1 EAN:	6417019926209

Technical

Cable Cross-Section:	Cu 0.75...2.5 mm ²
Conventional Free-air Thermal Current (I_{th}):	16 A
Conventional Thermal Current (I_{the}):	16 A
Mounting Type:	Base/DIN mounting
Power Loss:	at Rated Operating Conditions per Pole 0.9 W
Rated Insulation Voltage (U_i):	acc. to IEC 60947-1 690 V

Recommended Screw Driver:	Main Circuit Pozidriv 2
Terminal Type:	Screw Terminals
Tightening Torque:	acc. IEC 60947-1 0.8 N·m
Wire Stripping Length:	Main Circuit 8-10 mm Main Circuit 0.31-0.39 in

Technical UL/CSA

Wire Size:	18-14 AWG
Tightening Torque UL/CSA:	UL 7 lbf·in

Certificates and Declarations

CCC Certificate:	CCC AUX
Declaration of Conformity - CE:	1SCC390103D2701
UL Certificate:	CULUS AUXG

External Classifications and Standards

Object Classification Code:	Q
ETIM 9:	EC000041 - Auxiliary contact block
ETIM 10:	EC000041 - Auxiliary contact block
UNSPSC:	39121522
IDEA Granular Category Code (IGCC):	4743 >> Auxiliary contact block
eClass:	V11.1 : 27371302
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland):	3660441
E-Number (Norway):	4384790
E-Number (Sweden):	3172190

Categories

Products > Low Voltage Products and Systems > Switches > Switch Disconnectors

