



Main

| | |
|---------------------------|--|
| Range | ClimaSys |
| Product name | ClimaSys CV |
| Product or component type | Fan |
| Type of filter | Standard |
| Flow rate | Free flow rate with standard filter: 165 m ³ /h at 50 Hz Free flow rate with standard filter: 193 m ³ /h at 60 Hz |
| [Us] rated supply voltage | 175...253 V |
| Input voltage | 230 V 50/60 Hz |

Complementary

| | |
|---------------------------------------|---|
| Absorbed power | 16.3 W 50 Hz 14.3 W 60 Hz |
| [In] rated current | 0.12 A 50 Hz 0.94 A 60 Hz |
| Noise level < at | 50...51 dB |
| Bearing type | Ball |
| Height | 268 mm external: |
| Width | 248 mm external: |
| Depth | 104 mm external: |
| Cut-out dimensions | 223 x 223 mm |
| Net weight | 1.14 kg |
| Material | Outlet grille: injected thermoplastic (ASA PC) |
| Colour | Outlet grille: grey (RAL 7035) |
| Ambient air temperature for operation | -20...60 °C |
| Ambient air temperature for storage | -40...70 °C |
| Maximum pressure | 50 Pa flow rate 0 m ³ /h |
| Connections - terminals | Faston connector |
| IP degree of protection | IP54 |
| Device composition | 1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template 1 power cord |
| Condition of use | Overfrequent filter replacement should be avoided Filter must be cleaned and replaced regularly Flow rates depends on the work point, see ProClima software Outside temperature must be 5 °C lower than inside temperature Surrounding environment must be relatively clean |

Offer Sustainability

| | |
|------------------------|--------------------------------|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |

| | |
|----------------------------|--|
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
