

# EKSS16064

STAINLESS STEEL COMPACT VERSION, SINGLE DOOR ENCLOSURE



D	400
H	1600
Part No. AISI 304	EKSS16064
Part No. AISI 316L	EKSS16064-316*
W	600
Weight (kg)	81,9
h	1494
w	494
Item no.	EKSS16064

**Material:** AISI 304 pre-grained stainless steel / AISI 316L. Body and removable rear panel: 1.5 mm. Door: 2 mm. Bottom plate: 1.5 mm. Mounting plate: 3 mm galvanized steel.

**Body:** One piece enclosure body. Integrated depth profiles with hole pattern allowing mounting plate adjustable in depth.

**Door:** Surface mounted with 4 hinges allowing left or right hand opening. Including door frame with 25 mm hole pattern and earthing studs.

**Rear panel:** Fitted by M6 torx screws. Standard facilities for rear door mounting.

**Lock:** External espagnolette 4-point locking system. Standard fitted double-bit 3 mm insert. Standard inserts, cylinders, lift handles and T-handles are available as accessories.

**Bottom plates:** One piece bottom plate with injected polyurethane gasket to ensure maximum sealing.

**Mounting plate:** Double folded and slides into position. Adjustable in depth by steps of 25 mm. Mounting plate is delivered attached on the outside of the enclosure packaging.

**Earthing:** Door is equipped with separate welded earthing studs and earthing to the frame can be accomplished by using the ECF.

**Finish:** 240s pre-grained stainless steel (0.5 microns average).

**Protection:** Complies with IP 66 | TYPE 4X, 12, 13 | IK 10.

**Delivery:** One piece body with fitted door, bottom plate and mounting plate, including door earthing studs. Delivered on a pallet which is identical to the width of the enclosure. Mounting plate is attached to the outside of the enclosure packaging. All the packing material is recyclable.