

ARCA 604021W

Order symbol: ARCA 604021W
Product nbr: 8120132
Description: Cabinet, PC
Remarks: Cover with window, 2-point locking

EAN: 6418074080035
EI. number:
 Finland: 3423205
 Electric No. 8212091883
 Denmark:
 Electric No. Sweden: 2500152

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	600	400	210	MPP ARCA 6040
inch:	23.6	15.7	8.3	MPMP ARCA 6040

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term):	-40 ... 120 °C
Temperature °C (continuous):	-40 ... 80 °C
Temperature °F (short term):	-40 ... 250 °F
Temperature °F (continuous):	-40 ... 175 °F

Accessories:

MPS ARCA 6040	Mounting plate (550x350x2 mm)
---------------	-------------------------------

MPP ARCA 6040	Mounting plate perforated (550x350x2 mm - 26x11 mm)
MPMP ARCA 6040	Mounting plate multiperforated (550x350x2 mm - □3.6 mm)
MPX ARCA 6040	Mounting plate (550x350 mm)
DRS ARCA 604021	DIN rail frame set
DRS ARCA 604030	DIN rail frame set
IDS ARCA 6040	Inner door set
PMK ARCA 40	Pole mounting kit
RCS ARCA 6040	Rain canopy set
SBK ARCA 40	Support bar kit
SBK ARCA 60	Support bar kit
DSP ARCA VLS	Door stopper ARCA, vertical, left, small
DSP ARCA VRS	Door stopper ARCA, vertical, right, small

Rating:
 Ingress Protection (EN 60529): IP65
 Impact Resistance (EN 62262): IK08
 Electrical insulation: Totally insulated
 Halogen free (DIN/VDE 0472, Part 815): 1
 Flammability Rating: UL 94 5VA
 Glow Wire Test (IEC 695-2-1) °C: 960
 NEMA Class: NEMA 4, 4X, 12 and 13

Certificates:
 SGS Fimko

