



Available from the UK's premier enclosure distributor, iLECSYS Ltd,
01844 397300
sales@ilecsys.co.uk

iLECSYS have in-house capabilities to accurately machine enclosures of all sizes and materials.

Main

| | |
|---------------------------|--|
| Range | Thalassa |
| Product name | Thalassa PLA |
| Enclosure type | Multi-purpose |
| Product or component type | Suitable enclosure |
| Version | PLAZ |
| Nominal height | 750 mm |
| Nominal width | 750 mm |
| Nominal depth | 320 mm |
| Enclosure mounting | Floor-standing |
| Device composition | 1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 plinth |

Complementary

| | |
|-----------------------------|---|
| Body type | Sealed top and open bottom part assembled with side parts |
| Door type | Plain front |
| Number of doors | 1 door(s) |
| Door opening side | Reversible (120 °) |
| Lock type | 2 points handle lock, 5 mm double-bar |
| Accessibility for operation | Bottom Front Rear |
| Removable parts | Door by hinges Rear panel by fixing element |
| Material | Polyester reinforced with fibreglass |
| Colour | Grey (RAL 7035) |

| | |
|------------------------|-----------|
| Standards | IEC 62208 |
| Product certifications | Veritas |

Environment

| | |
|-------------------------------------|--|
| IP degree of protection | IP54 conforming to IEC 60529 (plinth type open bottom) |
| IK degree of protection | IK10 conforming to IEC 62262 (plain door) |
| Fire resistance | 960 °C conforming to IEC 62208 |
| Ambient air temperature for storage | -35...90 °C |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | Download RoHS China Declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|