Product datasheet Characteristics

NSYS3DM5415T

Spacial S3DM H500xW400xD150.IP66 IK10 RAL7035. Top & Bottom Gland Plate







Please note that image is indicative only of this type of enclosure. The part number NSYS3DM5415T is for the enclosure only and does not include the internal modular chassis. See NSYDLM range for chassis.

> Available from the UK's premier enclosure distributor, iLECSYS Ltd, 01844 397300 sales@ilecsys.co.uk

iLECSYS have in-house capabilities to accurately machine enclosures of all sizes and materials.

Main

Range	Spacial	
Product name	Spacial S3DM	
Application	Modular distribution application	:
Category	Compact enclosure	
Enclosure nominal height	500 mm	:
Enclosure nominal width	400 mm	
Enclosure nominal depth	150 mm	
Door type	Glazed	:
Mounting plate description	Without mounting plate	:
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Product destination	For installation of modular chassis DLM	
Device composition	2 cable gland plate: top and bottom 1 body 1 door 1 lock	:
	I IOCK	

Complementary

Number of doors Front face: 1 door(s) Door opening side Reversible (120 °) Lock type 3 mm double-bar lock Accessibility for operation Front Removable parts Door by hinges Cable gland plate by screws Material Body: steel Door: steel and security glass	Body type	Single piece body Gutter-shaped front rail double sheet thickness	90
Lock type 3 mm double-bar lock Accessibility for operation Front Removable parts Door by hinges Cable gland plate by screws Material Body: steel	Number of doors	Front face: 1 door(s)	
Accessibility for operation Front Removable parts Door by hinges Cable gland plate by screws Material Body: steel	Door opening side	Reversible (120 °)	to
Removable parts Door by hinges Cable gland plate by screws Material Body: steel	Lock type	3 mm double-bar lock	
Cable gland plate by screws Material Body: steel	Accessibility for operation	Front	
······································	Removable parts		si Social
	Material	•	lainer.

Surface finish	Epoxy-polyester powder
Colour	Grey (RAL 7035)
Standards	IEC 62208
Product certifications	CUL LR GL UL BV DNV

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	Download RoHS China Declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

- Contraction from the contraction of the contracti		
Warranty	18 months	