



Main

| | |
|---------------------------|---|
| Range | Spacial |
| Extended range | Spacial SF |
| Application | Multi-purpose |
| Product or component type | Suitable enclosure |
| Enclosure nominal height | 2000 mm |
| Enclosure nominal width | 800 mm |
| Enclosure nominal depth | 600 mm |
| Enclosure mounting | Floor-standing |
| Device composition | 1 door 1 mounting plate 1 rear panel 1 roof 1 structure 1 locking system with handle for door 2 sliding rails 4 mounting plate bracket |

Complementary

| | |
|-----------------------------|---|
| Structure type | Formed from a single section Panels and doors built into the structure Vertical uprights joined with top and bottom frames Perforated structure with a pitch of 25 mm |
| Door type | Plain on front |
| Number of doors | 1 on front |
| Door opening side | Reversible 120 ° |
| Lock type | 4 points lock, handle with 5 mm double bar insert on front door |
| Mounting plate description | Plain |
| Type of gland plate | Without gland plate |
| Accessibility for operation | Front Sides of enclosure Rear |
| Removable parts | Rear panel fixed by screws Roof fixed by screws Door fixed by screws for hinge Mounting plate bracket fixed by screws Sliding rail fixed by screws Mounting plate fixed by screws for mounting plate bracket |
| Material | Galvanised steel for frame Galvanised steel for uprights Polyamide 6 with 30 % fibre glass for handle Sheet steel for door Sheet steel for panels Zamak for hinge |
| Surface finish | Epoxy-polyester powder |
| Colour | Enclosure : grey RAL 7035 Handle : black RAL 9005 |

Environment

| | |
|-------------------------|------------------------------|
| Standards | IEC 62208 |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental Profile |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|