

Polyester floor-standing enclosures

Specific accessories

Fixing, cable-entry and other accessories

PB502909-38



PB502903-49



PB502904-29



PLAZ PLAZT

Characteristics		Canopy	Wall-fixing lugs	Cable-entry plate	
		<ul style="list-style-type: none"> It can be installed in all enclosure models. High resistance to impacts, temperature and bad weather. Increases the height (A) of the enclosure by 38 mm, without modifying its width or depth. 	Drilling positions and marks inside the side panels.	<ul style="list-style-type: none"> Easy drilling in specific customised version. Incompatibility with: adapter plates, step slides, internal door and chassis for modular distribution. 	
Material		Polyester reinforced with fibreglass	Carbon steel with passivated zinc-coated	Polyester reinforced with fibreglass	
Colour		RAL 7035 grey	-	RAL 7035 grey	
Thickness		-	-	4 mm	
Ingress protection rating		-	-	IP00	
Installation		Essential for outdoor use	-	-	
Fixing		-	<ul style="list-style-type: none"> Fixing on the sides by 4 or 6 lugs in horizontal position (6 lugs for enclosures with height ≥ 1000 mm) 10 mm fixing distance on the rear of the enclosure plane 	-	
Maximum load inside enclosure		-	180 kg, including weight of enclosure	-	
Supply		Delivered with the fixings required for installation	Set of 6 lugs and fixings	Delivered with the fixings required for installation	
Width (mm)	Depth (mm) (C)	References			
500	320	NSYTJPLA53G	NSYFMPLA	NSYECPLAZ53G	
750	320	NSYTJPLA73G		NSYECPLAZ73G	
1000	320	NSYTJPLA103G		NSYECPLAZ103G	
1250	320	NSYTJPLA123G		NSYECPLAZ123G	
500	420	NSYTJPLA54G		NSYECPLAZ54G	
750	420	NSYTJPLA74G		NSYECPLAZ74G	
	620	NSYTJPLA76G		NSYECPLAZ76G	
1000	420	NSYTJPLA104G		NSYECPLAZ104G	
1250	420	NSYTJPLA124G		NSYECPLAZ124G	
	620	NSYTJPLA126G		NSYECPLAZ126G	
					<p>Cable-entry plate</p> <ul style="list-style-type: none"> 1-door enclosure 2-door enclosure

(1) For enclosures with height ≥ 1000 mm, 1 extra lug at the centre of the A-375 side.

PLAT PLAZT

PB502910-25



PB500191-25



Characteristics		Grille for IP54 instead of IP44	Renovation and anti-graffiti paint	
		1 grille for 500 and 750 mm wide enclosures, 2 grilles for 1000 and 1250 mm wide enclosures. Prevents the entry of dust and provides the enclosure with IP 5X protection at the top. Maintains the possibility of ventilation.	2-component paint system, specially formulated for polyester enclosures. Renews enclosures and allows easy removal of graffiti. Paint composed of: base (80 %) and hardener (20 %).	
Colour		RAL 7035 grey	RAL 7035 grey	
Installation		It is installed from the inside in the upper ventilation opening	-	
Supply		Delivered with G2 M1 standard synthetic filter, see ClimaSys section	1 kg: <ul style="list-style-type: none"> 800 g tin of base paint 200 g tin of hardener (Coverage = 5 m ²)	5 kg: <ul style="list-style-type: none"> 4 kg tin of base paint 1 kg tin of hardener (Coverage = 25 m ²)
References		NSYCAG125LPF	NSYAUPG1G	NSYAUPG5G
				NSYAUPGS