



Sample photo

Order symbol: PC 95/35 LT
Product nbr: 6012931
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074054654
El. number:
 Finland 3421368
 Denmark 8212027695

Including: Base with PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:			L		W		H		Rating:		
mm:	100	100							Ingress Protection (EN 60529): IP 66/67		
inch:	3.9	3.9							Impact Resistance (EN 50102): IK 08		
Materials:										Electrical insulation: Totally insulated	
Material:	PC								Halogen free (DIN/VDE 0472, Part 815): Yes		
Base colour:	RAL 7035								UV resistance: UL 508		
Cover colour:	Smoked grey								Flammability Rating (UL 746 C 5): UL 94 5V		
Cover screws material:	Polyamide								Glow Wire Test (IEC 695-2-1) °C: 960		
Cover screws colour:	Black								NEMA Class: NEMA 1, 4, 4X, 6, 12, 13		
Gasket material:	Polyurethane								Certificates:		
Temperatures:										Germanischer Lloyd (GL)	
Short term:	-40 ... 120 °C								Underwriters Laboratories		
Continuous:	-40 ... 80 °C								Det Norske Veritas		
Short term:	-40 ... 250 °F								Fimko		
Continuous:	-40 ... 175 °F								Europe EN 50298 1998		
Accessories:										UL Canada	
MIV 95	Mounting plate								Gost R		
B-3	DIN-35 Mounting rail										

