



Sample photo

**Order symbol:** PC 95/50 LT  
**Product nbr:** 6012932  
**Description:** Enclosure, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074054661  
**El. number:**  
 Finland 3421370  
 Denmark 8212027718

**Including:** Base with PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:			L	W	H	Rating:
mm:			100	100	50	<b>Ingress Protection (EN 60529):</b> IP 66/67
inch:			3.9	3.9	2	<b>Impact Resistance (EN 50102):</b> IK 08
Materials:						
<b>Material:</b>			PC			
<b>Base colour:</b>			RAL 7035			
<b>Cover colour:</b>			Smoked grey			
<b>Cover screws material:</b>			Polyamide			
<b>Cover screws colour:</b>			Black			
<b>Gasket material:</b>			Polyurethane			
Temperatures:						
<b>Short term:</b>			-40 ... 120 °C			
<b>Continuous:</b>			-40 ... 80 °C			
<b>Short term:</b>			-40 ... 250 °F			
<b>Continuous:</b>			-40 ... 175 °F			
Accessories:						
MIV 95			Mounting plate			
B-3			DIN-35 Mounting rail			
			<b>Electrical insulation:</b> Totally insulated <b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes <b>UV resistance:</b> UL 508 <b>Flammability Rating (UL 746 C 5):</b> UL 94 5V <b>Glow Wire Test (IEC 695-2-1) °C:</b> 960 <b>NEMA Class:</b> NEMA 1, 4, 4X, 6, 12, 13			
Certificates:						
			Germanischer Lloyd (GL) Underwriters Laboratories Det Norske Veritas Fimko Europe EN 50298 1998 UL Canada Gost R			

