



Sample photo

Order symbol: PCM 95/60 T
Product nbr: 6016931
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074054791
EI. number:
 Finland 3421396
 Denmark 8212027572

Including: Base with metric knock-outs and PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:			Rating:
L	W	H	
mm:	100	100	Ingress Protection (EN 60529): IP 66/67
inch:	3.9	3.9	Impact Resistance (EN 50102): IK 08
Materials:			
Material:	PC		Electrical insulation: Totally insulated
Base colour:	RAL 7035		Halogen free (DIN/VDE 0472, Part 815): Yes
Cover colour:	Smoked grey		UV resistance: UL 508
Cover screws material:	Polyamide		Flammability Rating (UL 746 C 5): UL 94 5V
Cover screws colour:	Black		Glow Wire Test (IEC 695-2-1) °C: 960
Gasket material:	Polyurethane		NEMA Class: NEMA 1, 4, 4X, 6, 12, 13
Temperatures:			Certificates:
Short term:	-40 ... 120 °C		Germanischer Lloyd (GL)
Continuous:	-40 ... 80 °C		Underwriters Laboratories
Short term:	-40 ... 250 °F		Det Norske Veritas
Continuous:	-40 ... 175 °F		Fimko
Accessories:			Europe EN 50298 1998
MIV 95	Mounting plate		UL Canada
B-3	DIN-35 Mounting rail		Gost R

